



WO 9603311A1 INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COUPERATION TREATT (PCT)

(51) International Patent Classification 6:

B63B 59/04, C09D 5/16

(11) International Publication Number:

WO 96/03311

(43) International Publication Date:

8 February 1996 (08.02.96)

(21) International Application Number:

PCT/SE95/00894

A1

(22) International Filing Date:

28 July 1995 (28.07.95)

(30) Priority Data:

9402584-8

28 July 1994 (28.07.94)

(71) Applicant (for all designated States except US): SEALFLOCK AKTIEBOLAG [SE/SE]; P.O. Box 1006, S-430 90 Öckerö

(72) Inventor; and

(75) Inventor/Applicant (for US only): FORSBERG, Gunnar [SE/SE]; Askims Domarringsväg 113, S-436 38 Askim

(74) Agent: CLAESSON, Lennart, Patent Ability L Claesson AB, P.O. Box 4110, S-175 04 Järfälla (SE).

(81) Designated States: AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, JP, KE, KG, KP, KR, KZ, LK, LR, LT, LU, LV, MG, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TT, UA, UG, US, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, MW, SD, SZ, UG).


Published

With international search report.

(54) Title: FOULING PROTECTION FOR CONSTRUCTIONS IN WATER

(57) Abstract

By using natural marine substances which are overgrowth preventing a very efficient protection can be obtained without use of environmental toxines. Examples of such natural substances are such being based on seaweed, in which there is a substance that prevents overgrowth, or such based on bacteria or other microorganisms which either themselves prevent, absorb or gormandize on harmful plants or animals or contain a substance that prevents overgrowth. These substances are bound to the marine construction either by this being made of a fibre material or by it being provided with a surface layer of a fibre material.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	LE	Ireland	NZ	New Zealand
B.J	Benin	П	Italy	PL	Poland
BR	Brazil	JР	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG -	Kyrgystan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic	SD	Sudan
CG	Congo		of Korea	SE	
CH	Switzerland	KIR	Republic of Korea	SI	Sweden
CI	Côte d'Ivoire	KZ	Kazakhstan	SK	Slovenia
CM	Cameroon	II.	Liechtenstein		Slovakia
CN	China	LK	Sri Lanka	SN	Senegal
cs	Czechoslovakia	LU	Luxembourg	TD	Chad
cz.	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC		TJ	Tajikistan
DK	Denmark	MD	Monaco	17	Trinidad and Tobago
ES	Spain		Republic of Moldova	UA	Ukraine
n .	Finland	MG	Madagascar	us	United States of Americ
TR.	Prance	ML	Mali	UZ	Uzbekistan
GA.	Gabon	MN	Mongolia	VN	Vict Nam

Fouling protection for constructions in water.

Field of the invention:

The present invention refers to ships and other marine constructions which at least partly extend below the water surface. The word "marine" is here used not only for objects in sea water but also in sweet water in lakes, rivers etc. The invention particularly refers to treatment of surfaces below the water line to prevent fouling and maintain low friction for parts that move in the water. The invention also refers to treatment for preventing overgrowth on fishing tackle and other constructions that primarily are made of fibre material.

15 State of the art:

In order to prevent fouling of plants, animals and other organisms on ships and other marine constructions until now one has mainly used toxic colors. As is evident from the patent application WO, A1, 93/25432 one has also tested to cover surfaces, that are exposed to fouling, with fibre flock, which until now has proved to give good results.

The technical problem:

In some environments with extremely severe fouling merely coating with fibre flock on the hull surfaces has not given a sufficiently good protection. In certain cases, a completion of the protection can be needed. Today, nor for fishing nets and similar constructions made of fibres of synthetic or other materials there is found any good anti-fouling protection.

The solution:

By using natural marine substances that are overgrowth preventing, a very efficient protection can be obtained without need for environmental toxines to be utilized. Examples of such natural substances are such that are based on seaweed, in which a substance is present that prevents overgrowth, or such that are based on bacteria or other microorganisms that either themselves prevent, absorb or

35

2

gormandize on harmful plants or animals or contain a substance that prevents overgrowth. These substances are bound to the marine construction either by this being made of a fibre material or by it being provided with a surface layer of a fibre material.

By means of fibres that are flocked by known technique an active surface is formed that can be enlarged by 30-50 times in relation to the area of the base. It has also turned out that the fibre flock form an appropriate environment for different types of bacteria and other microorganisms. Bacteria which have a favourable influence on those plants or animals which constitute a problem are previously known, but before the origin of the present invention it has not been possible to create an environment in which the bacteria is retained on a surface so that a long-term action is obtained.

A fibre flocked surface has proved to form such an environment that solves the problem to retain active substances, waxes, bacteria or other microorganisms on surfaces which are located in connection to or under the water. The problem of severe overgrowth on for instance hull surfaces is solved by a fibre flocked surface in which an appropriate substance, bacteria or other microorganisms have been added.

The method to cover a surface with fibre flock is well known. It consists in that a surface first is coated with an adhesive whereupon electrically charged fibres are made to land in the adhesive and stick there. The adhesive is often a resin glue and the fibres are generally synthetic fibres of for instance polyamide.

However, the fibres which may come into question for the present invention are not limited to any special type, but also for instance coal fibres, glass fibres or non-synthetic fibres may be suitable. Especially to retain bacteria such fibres are suitable that bind a smaller amount of water such as for instance polyamide, which normally absorbs 2 - 4 % of

10

15

20

25

water. Even hollow fibres can be expected to have good characteristics to retain these substances and organisms.

In a preferred embodiment of the present invention a large amount of fibres is utilized which by electrostatic application to a large part will be fixed perpendicularly against the base. The fibre density can be in the range of 50-300 fibres per square mm, preferably more than 150 fibres per square mm, with a fibre thickness less than 0.1 mm, preferably less than 0.05 mm and a length in the range of 0.5-5 mm, preferably less than 3 mm.

In a second preferred embodiment the marine construction in itself is made of a yarn or a net of fibre material, whereby the fibre length is a good deal longer. Since these fibres are of an appropriate type to bind the actual anti-fouling substance, no fibre flock is required to obtain the intended effect according to the invention. In other cases a fibre flocking can be appropriate even when the marine construction is of fibre material.

Bacteria that can be used in connection with the present invention can for instance be of the family Alteromonas, but also other bacteria or microorganisms can be used according 25 to the invention. The bacteria can be applied on surf that are made of fibre material or which earlier have costed with fibr flock, but it is also possible 10 pilireat the fibres with ..he bacteria in question before they are applied through flocking or before they are processed to a yarn, net or the like. It is probably possible to retain the 30 culture of bacteria in the fibre flocked surface during a long period, even during periods of winter keeping during cold weather and the like. Bacteria which can be of interest in this connection can be kept freeze-dried during a long period. Other substances can also either be applied on 35 earlier fibre flocked surfaces or be added to the fibre before this is applied.

Advantages:

Owing to the present invention one attains the advantage that less energy is required to operate a ship without overgrowth, which means cost savings and less stress on the environment.

5 Since boats and other marine constructions are provided with natural anti-fouling substances, bacteria or other microorganisms in fibre material of which the constructions are built or in fibre flock which has been applied on surfaces under the water line, this counteracts growth of algae and other growths and animals on the surfaces. One can therefore dispense with the use of toxic substances such as red lead to avoid such growth. This further strengthens the environmental promotion effect of the invention.

15 Examples:

Tests with bacteria and seaweed on flocked surfaces have been carried out and are described with reference to the drawings in which

- Figure 1 shows schematically bacteria adhered to fibers,
- 20 Figure 2 shows an electron micrograph photo of D2 cells colonizing the outer part of a bunch of fibres,
 - Figure 3 shows D2 cells colonizing fibres inside a bunch of fibres,
- Figures 4 and 5 show close up photos of D2 cells colonizing a fibre,
 - Figure 6 shows samples from test with bacteria D2, and Figure 7 shows samples from test with seaweed Delicea.

Tests with bacteria D2.

30 Flock was put into a bacteria suspension for approx. 36 hours in room temperature. This is the normal procedure. Then the fibres were washed in a salt (NaCl). The fibres and the bacteria were then fixed in 2.5% gluteraldehyd in 0.1M Na cacodylate buffer and later in 2% osmium tetraoxide. The samples were washed in ethanol (from 50% to 100%) and transferred to 100% acetone. In between these tests the samples were also mechanically tested by putting them into a centrifugal device. This shows that the bacteria colonize the fibers strongly and very successfully. In Figure 1 is

schematically shown colonies of bacteria 1 on flocked fibres 2 fixed on a base 4 by means of an adhesive 3. Electron micrograph photos of Figures 2 to 5 show the colonizing of bacteria D2 on polyamid 6.6 fibres. This test was made at the New South Wales University in Sydney, Australia.

Tests with bacteria D2 and seaweed, Delicea at sea in Sydney, Australia.

Tubes with various types of flockfibres where coated with extract from D2 and Delicea. Untreated tubes having only flockfibers where put into the sea together with the treated tubes for a period of 7 weeks in an area with controlled and severe fouling in Sydney, Australia. In Figures 6 and 7, tubes C are control tubes with untreated flock, tube B in Figure 6 is treated with bacteria D2, tube A in Figure 7 is also treated with Seaweed Delicea.

The effect of both bacteria and extracts were analysed after the testing period and the addition of both bacteria and seaweed extract enhanced the overall effect of soft fouling as bryozonas, hydroids. In some instances the total percent cover of organisms on treated flocks were less than 1%.

The invention is not limited to the above embodiments but can be varied in different ways within the scope of the patent claims.

6

CLAIMS

- A method for preventing fouling on ships and other constructions in water, wherein natural substances, waxes,
 bacteria or other microorganisms that inhibit fouling are added to at least parts of the ships or other constructions, which consist of or have been coated with fibre material.
- A method according to claim 1, wherein the fibre material
 consists of fibre flock.
 - 3. A method according to claim 2, wherein the fibre flock consists of synthetic textile fibres applied in an adhesive on the surfaces with an electrostatic application technique.
- 4. A method according to claim 2 or 3, wherein the length of the fibres is between 0.5 and 5 mm and a density range of 50-300 fibres per square mm.
- 20 5. A method according to any of claims 1-4, wherein the substance is extracted from seaweed.
 - 6. A method according to any of claims 1-4, wherein the bacteria are of the family Alteromonas.
 - 7. A ship or other marine construction wholly or partially made of fibre material or provided with fibre flock on those surfaces which come in contact with the water, wherein natural substances, waxes, bacteria or other microorganisms that inhibit overgrowth by plants, animals and/or harmful microorganisms are added to the fibre or at least parts of the fibre flocked surfaces.
 - 8. A ship or other marine construction according to claim 7, mainly made of yarn or net of long fibres.
 - 9. A ship or other marine construction according to claim 7 or 8, wherein the fibre flock consists of synthetic fibres

2.5

7

which are applied in an adhesive on the surfaces with an electrostatic technique.

- 10. A ship or other marine construction according to claim 9, wherein the synthetic fibres in the fibre flock has a length between 0.5 and 5 mm and a density range of 50-300 fibres per square mm.
- 11. A ship or other marine construction according to any of claims 7-10, wherein the substance is extracted from seaweed.
 - 12. A ship or other marine construction according to any of claims 7-10, wherein the bacteria are of the family Alteromonas.

13. The use of natural substances, waxes, bacteria or other microorganisms for inhibiting ongrowth on ships or other marine constructions in combination with long fibres or fibre flock which constitute carrier for the substances, the

20 bacteria or the other microorganisms.




Fig. 2





Fig. 4




Fig. 5








Fig. 6



BNSDOCID: <WO___9603311A1_I_>

Fig. 7





International application No.

PCT/SE 95/00894

A. CLA	SSIFICATION OF SUBJECT MATTER		
	SOURCE WATTER		
IPC6:	B63B 59/04, C09D 5/16		
According	B63B 59/04, C09D 5/16 to International Patent Classification (IPC) or to b	oth national classification and IPC	
D. 11LL	DS SEARCHED		
Minimum	documentation searched (classification system follow	wed by classification symbols)	
IPC6:	B63B, C09D, B05D		
CE DI	ation searched other than minimum documentation	to the extent that such documents are included	in the fields searched
SE,DK,	FI,NO classes as above		
Electronic	data base consulted during the international search (name of data base and where precioable con-	
		where practicable, sear	cn terms used)
C DOS:	11.47	·	
	MENTS CONSIDERED TO BE RELEVAN	NT.	
Category*	Citation of document, with indication, where	appropriate, of the relevant passage	Palana
A		T-0-1	Relevant to claim
^	WO 9325432 A1 (JURISTBYRAN INT 23 December 1993 (23.12.93	DIREKT AB),	1,7
	== 000cmBc(1333 (23.12.93	3)	1
	700000		
ĺ			
ĺ			
1			
ļ			
1			•
1			•
1			
		1	
Further	documents are listed in the continuation of B	ox C. X See patent family annex.	
	tegories of cited documents:	T later document published after the intere	ational filing data or price
to be of pa	defining the general state of the art which is not considered articular relevance	the principle or theory underlying the in	
document	ment but published on or after the international filing date	"X" document of particular relevance: the ci-	imad in
cited to est	which may throw doubts on priority claim(s) or which is ablish the publication date of another citation or other	considered novel or cannot be considered step when the document is taken alone	d to involve an inventive
-promat roa	son (as specified) referring to an oral disclosure, use, exhibition or other	"Y" document of particular relevance: the cla	simed invention cannot be
		combined with one or more other such d	occument is
the priority	oublished prior to the international filing date but later that date claimed	being obvious to a person skilled in the a "&" document member of the same patent far	LTI.
e of the ac	ctual completion of the international search		
•		Date of mailing of the international sea	rch report
Octobe	r 1995	1 3 - 11 - 19 95	
ne and ma	iling address of the ISA/	Authorized officer	
dish Pat	ent Office	Onice	
imile No	102 42 STOCKHOLM + 46 8 666 02 86	Johan von Döbeln	
		Telephone No. +46 8 782 25 00	

INTER	NATIONAL SI	EARCH REPORT	28/08/95	International application No. PCT/SE 95/00894		
Patent cited in se	document earch report	Publication date	Patent family member(s)		Publication date	
WO-A1-	9325432	23/12/93	NONE			
	·					
		·				